KHX1333C9D3B1K2/2G

2GB (1GB 128M x 64-Bit x 2 pcs.) DDR3-1333MHz CL9 240-Pin DIMM Kit

DESCRIPTION:

Kingston's KHX1333C9D3B1K2/2G is a kit of two 128M x 64-bit (1GB) DDR3-1333MHz CL9 SDRAM (Synchronous DRAM) memory modules, based on eight 128M x 8-bit DDR3 FBGA components per module. Total kit capacity is 2GB. The SPDs are programmed to JEDEC standard latency DDR3-1333MHz timing of 9-9-9 at 1.5V. Each 240-pin DIMM uses gold contact fingers and requires +1.5V. The JEDEC standard electrical and mechanical specifications are as follows:

FEATURES:



- ☑ JEDEC standard 1.5V ± 0.075V Power Supply
- ☑ VDDQ = 1.5V ± 0.075V
- ☑ 667MHz fCK for 1333Mb/sec/pin
- ☑ 8 independent internal bank
- ☑ Programmable CAS Latency: 5,6,7,8,9,10
- ☑ Posted CAS
- ☑ Programmable Additive Latency: 0, CL - 2, or CL - 1 clock
- ☑ Programmable CAS Write Latency(CWL) = 7(DDR3-1333)
- ☑ 8-bit pre-fetch
- ☑ Burst Length: 8 (Interleave without any limit, sequential with starting address “000” only), 4 with tCCD = 4 which does not allow seamless read or write [either on the fly using A12 or MRS]
- ☑ Bi-directional Differential Data Strobe
- ☑ Internal(self) calibration : Internal self calibration through ZQ pin (RZQ : 240 ohm ± 1%)
- ☑ On Die Termination using ODT pin
- ☑ Average Refresh Period 7.8us at lower then TCASE 85°C, 3.9us at 85°C < TCASE . 95°C
- ☑ Asynchronous Reset
- ☑ PCB : Height 1.180” (30.00mm), single sided component

PERFORMANCE:

☑ CL(IDD)	9 cycles
☑ Row Cycle Time (tRCmin)	49.5ns (min.)
☑ Refresh to Active/Refresh Command Time (tRFCmin)	110ns
☑ Row Active Time (tRASmin)	36ns (min.)
☑ Power	1.080 W (operating per module)
☑ UL Rating	94 V - 0
☑ Operating Temperature	0° C to 85° C
☑ Storage Temperature	-55° C to +100° C

Preliminary

MODULE DIMENSIONS:





w/ Heatsink Assembly